

C2TA521080IPOE



- 2 Megapixel – Full 1080p
- H.264 High Profile 4.2
- 12 IR LEDs
- 12VDC / POE
- ONVIF Compliant
- 2 Year Warranty



H.264 High Profile 4.2 Compression

- Most efficient compression technology available
- Better picture quality
- More storage

Fast MegaPixel Image Rates

- Up to 30fps in Full HD 1080p Mode

Multi-Streaming

- Up to 3 simultaneous independent streams
- Two H.264, One MJPEG
- Each stream configurable independently
 - Frames per second
 - Resolution
 - Quality
 - Send to different source

Mini SD Slot

- Record directly to SD card on alarm
- Supports > 2gb card

ONVIF Compliance

- Fully compliant with ONVIF industry standards

Digital Zoom

- Zoom live or after event while recording full field of view in HD

Real Time Streaming Protocol (RTSP)

- Allows for compatibility with media players such as Apple QuickTime®, Windows Media Player®, VLC Player®, etc.

Alarm Contacts

- Direct Input/Output triggers
- RS485 output
- Trigger alarm events to PTZ

Viewbiquity M2M (Machine to Machine) Compliance

- www.viewbiquity.com



Technical Specifications



Camera	C2TA521080IPOE
Resolution	Full HD 1080p
Effective Pixels (H x V)	1980 x 1080, 1280 x 720, 640 x 360
Video Compression	H.264 High Profile Level 4.2, MJPEG
Image Sensor	Progressive Scan CMOS with Removable ICR, True Day/Night
Frame Rate	Up to 30 frames per second in Full HD 1080p Mode
Network	10/100 Base-T (RJ-45)
Alarm Contacts	1 Channel Input / Output
Audio	Full Duplex Audio Connection (mic and speaker sold separately)
Audio Compression	G.711
Storage	Record to ONVIF NVR, FTP, NFS, CIFS, or Mini SD
Privacy Masking	Yes
Protocol	ONVIF
Network Protocol	SMTP – Email Notification, Multi-Casting, RTSP / RTP / RTCP, TCP / UDP, HTTP, DHCP, PPPoE, DDNS, NTP
Minimum Illumination	1 Lux / F1.2 w/o IR 0.0 Lux with IR
Megapixel Varifocal Lens Included	2.8-10 mm
Infrared	12 IR LED's, 10-15M Distance
Motion Detection	Yes
Analog Video Output	Yes
Power Requirements	12VDC / PoE
Clear2there reserves the right to change products or specifications without notice	

Optional Accessories:



C2TA5WALL



C2TA5PEB



C2TA5OCM



C2TA5POB



C2TA5ADPT