## C2TA55MPIPOE



- 5 Megapixel (2592 x 1920)
- H.264 High Profile 4.2
- 12 IR LEDs
- 12VDC / POE
- ONVIF Compliant
- IP66 / IK10 Rated
- 2 Year Warranty



## H.264 High Profile 4.2 Compression

- Most efficient compression technology available
- Better picture quality
- More storage

## Fast MegaPixel Image Rates

- 10fps in 2592 x 1920
- Up to 30fps in Full HD 1080p Mode

## **Multi-Streaming**

- Up to 3 simultaneous independent streams
- Two H.264, One MJPEG
- Each stream configurable independently
  - Frames per second
  - Resolution
  - Quality
  - Send to different source

#### Mini SD Slot

- Record directly to SD card on alarm
- Supports up to 64gb card

## **ONVIF Compliance**

Fully compliant with ONVIF industry standards

#### **Digital Zoom**

 Zoom live or after event while recording full field of view in HD

#### Real Time Streaming Protocol (RTSP)

 Allows for compatibility with media players such as Apple QuickTime®, Windows Media Player®, VLC Player®, etc.

#### **Bandwidth Optimization**

- 6 fps (in optimization mode)
- Up to 4x Less Bandwidth

# Viewbiquity M2M (Machine to Machine) Compliance

www.viewbiquity.com







Technical Specifications	
	E STATE OF THE STA
Camera	C2TA55MPIPOE
Resolution	5 Megapixel
Effective Pixels (H x V)	2592 x 1920, 1980 x 1080, 1280 x 720, 640 x 360
Video Compression	H.264 High Profile Level 4.2, MJPEG
Image Sensor	Progressive Scan CMOS with Removable ICR, True Day/Night
Frame Rate	10fps (Up to 30 fps in Full HD 1080p Mode)
Network	10/100 Base-T (RJ-45)
Alarm Contacts	1 Channel Input / Output
Audio	1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G.711
Storage	Record to ONVIF NVR, FTP, NFS, CIFS, or Mini SD
Privacy Masking	Yes
Protocol	ONVIF
Network Protocol	SMTP – Email Notification, Multi-Casting, RTSP / RTP / RTCP, TCP / UDP, HTTP, DHCP, PPPoE, DDNS, NTP
Minimum Illumination	0.5 Lux / F1.2 w/o IR 0.0 Lux with IR
Megapixel Varifocal Lens Included	3.3-12 mm
Infrared	12 IR LED's, 10-15M Distance
Motion Detection	Yes
Analog Video Output	Yes
Power Requirements	12VDC / PoE
Temperature	-10° - 55° C
Clear2there reserves the right to change products or specifications without notice	

## Optional Accessories:



C2TA5WALL



C2TA5PEB



C2TA5OCM



C2TA5POB



C2TA5ADPT