



CLEAR2THERE 12MP FISHEYE CAMERA



C2TFE12MPIPOE

- > 12 Megapixel
- > 360° Field of View
- > 6 IR LEDs, 15m Range Smart IR
- > Unique De-Warping Image
- > 1.83mm Lens
- > HLC / Defog / dWDR
- > 12VDC / 24VAC / POE
- > One Year Warranty

TECHNICAL SPECIFICATIONS

Max Resolution	12MP (4000×3000)
Video Compression	H.264 High/Main/Baseline Profile
Bitrate	Stream1: 500kbps~16000kbps, Stream2: 100kbps~8000kbps, CBR/VBR
Image Sensor	1/1.7" Progressive Scan CMOS
Lens	1.83mm Lens, 360° FOV
De-Warping	1F+3/5/7, 180° Panorama
Infrared	6pcs, 15m Range Smart IR
Image Enhancement	HLC / Defog / dWDR
Digital Noise Reduction	2D/3D DNR
Audio I/O	1ch Audio In, 1ch Audio Out
Alarm I/O	1ch Alarm In, 1ch Alarm Out
Protocol	ONVIF
Network Protocol	SMTP – Email Notification, Multi-Casting, RTSP / RTP / RTCP, TCP / UDP, HTTP, DHCP, PPPoE, DDNS, NTP
Edge Storage	Micro SD/SDHC/SDXC slot, Max 128GB
Operating Temperature	Starting: -30°C ~ 60°C (-22°F ~ 140°F), Working: -40°C ~ 60°C (-40°F ~ 140°F)
Power Requirements	DC12V/POE/AC24V
Power Consumption	5W (IR LED OFF), 8W (IR LED ON)
Ratings	IP67

Clear2there reserves the right to change products or specifications without notice.



CLEAR2THERE
2904 West 10th Street
Sioux Falls, SD 57104

Tel: 605.777.7006
Email: info@clear2there.com
Web: www.clear2there.com